

Robust & reliable 137kW indirect fired heater, perfect for delivering fast & effective heating to marquees, warehouses, workshops & industrial units.

- Burner cover: protects the burner against blows, dust, water, weather & collects diesel fuel
- Burner supplied with snorkel jack to ensure clean air combustion through connection with outdoor air uptake duct
- Heat exchanger designed with high performance fans which ensure high efficiency
- Sturdy attachment rods allow for movement on any floor
- Bearing structure with removable panels for interior washing
- Panels with reinforcement cross pleats to ensure superior rigidity & strength
- Ventilator conforms with European directives
- Low sound level - below 67db at 2 metres
- 7-blade fan with high performance for uniform diffusion of warm air through duct
- Control rear electrical panel - Supplied with a sturdy metal cover to prevent damage & unauthorized access
- Service front electrical panel - Located inside the burner cover lid to prevent contact with dust, water & snow



| Detail                | Jumbo 145                  |
|-----------------------|----------------------------|
| Heat Output           | 137kW                      |
| Temperature Increase  | 48 degrees                 |
| Power Supply          | 230 V/50 Hz                |
| Plug Type             | 16A 3 Pin BS4343           |
| Fan Type              | -                          |
| Max Current           | -                          |
| Air Flow              | 12,000M <sup>3</sup> /hour |
| Air Pressure          | -                          |
| Outlet Diameter       | 600mm                      |
| Max Duct Length       | 6M                         |
| Weight                | 260kg                      |
| Dimensions (WxLxH) mm | 890 x 1905 x 1354          |
| Fuel Consumption      | 11.45 litres/hour          |
| Sound Level           | <67db at 2 metres          |