

The 150kW Chiller is suitable for a complete range of cooling applications – air conditioning, process cooling and even ice rink creation.

- Water Outlet Temperature Regulator
- Automatic Fan Circuit Breaker
- Fan Speed Regulator
- Internal Fan Protection Grid
- Water Expansion Vessel
- 3 Bar Water Pump
- Buffer Tank
- Steel Framed
- Electric Board Heater
- Water Strainer
- Electronic Expansion Valve
- Condensing Coil Grid with Metallic Strainer



Detail	LCX164CSG	
Performance Data	Duty	152.3kW
	Inlet Temperature	12°C
	Outlet Temperature	7°C
	Ambient	35°C
	Compressor Power	52.5kW
	EER	2.73
	Compressors	4
	Compressor Type	Scroll
	Capacity Steps	4
	Noise Level	59dB(A)
	Dry Weight	1055kg
	Dimensions mm (WxLxH)	1185x3190x1720
	Control	Automatic Programme
	Buffer Tank Capacity	340 litres
	Water Connection	2" Bauer Male & Female
	Water Pump	Yes
Refrigerant	Type	R410a
	No. Of Circuits	2
Evaporator	Type	Plate
	No Of Circuits	2
	Design Flow	-
	Pressure Drop	-
	Max System Pressure	-
Condensor	Fan Quantity	3
	Fan Type	Axial
Electrical	Power Supply	400-3-50
	Running amps	
	Power Consumption	55.8 kW
	Full Load Amps	131 Amps
	Start Amps	330 Amps
	Total Current LPA	
Unit Connection	Hard Wired	

**Call us now 0808 1691919 for an instant quote**