

The 150kW Chiller is suitable for a complete range of cooling applications – air conditioning, process cooling and even ice rink creation.

- Water Outlet Temperature Regulator
- Automatic Fan Circuit Breaker
- Fan Speed Regulator
- Internal Fan Protection Grid
- Water Expansion Vessel
- 3 Bar Water Pump
- Buffer Tank
- Steel Framed
- Electric Board Heater
- Water Strainer
- Electronic Expansion Valve
- Condensing Coil Grid with Metallic Strainer



Detail	LCX164CSG	
Performance Data	Duty	152.3kW
	Inlet Temperature	12°C
	Outlet Temperature	7°C
	Ambient	35°C
	Compressor Power	52.5kW
	EER	2.73
	Compressors	4
	Compressor Type	Scroll
	Capacity Steps	4
	Noise Level	59dB(A)
	Dry Weight	1055kg
	Dimensions mm (WxLxH)	1185x3190x1720
	Control	Automatic Programme
	Buffer Tank Capacity	340 litres
	Water Connection	2" Bauer Male & Female
	Water Pump	Yes
Refrigerant	Type	R410a
	No. Of Circuits	2
Evaporator	Type	Plate
	No Of Circuits	2
	Design Flow	-
	Pressure Drop	-
	Max System Pressure	-
Condensor	Fan Quantity	3
	Fan Type	Axial
Electrical	Power Supply	400-3-50
	Running amps	
	Power Consumption	55.8 kW
	Full Load Amps	131 Amps
	Start Amps	330 Amps
	Total Current LPA	
Unit Connection	Hard Wired	

Call us now 0808 1691919 for an instant quote