

Technical specification for: **2MW Containerised Boiler**

2MW containerised boiler hire capable of delivering heating and hot water for emergency or planned maintenance fast efficient and easy to install suitable for a variety of applications.



Performance Data

Output	2,000 kW
Temperature Range	30-90 °C
Variable Temperature Control	Yes
Max Working Pressure (Safety Valve)	4 Bar
BMS Outputs	No
Time Clock	Yes
Frost Protection	No
Flow	80 m ³ /hr
Expansion Vessel	2000 ltrs

Fuel

Fuel Type	Diesel Oil/Natural Gas
Fuel Connection (Oil)	0.5" Flat Face Hydraulic
Fuel Consumption (Oil)	180 ltrs/hr
Fuel Connection (Gas)	PN16 DN100 Flange
Fuel Consumption (Gas)	200 m ³ /hr
Temp. Gas Pipe Size	4"
Gas Trac Maximum Length	9 mtrs

System Connections

Flexible Hose Connections	Flow/Return
Flexible Hose Connection Type	PN16 Flange
Water Connections	6" DN150
DHW System	External

Electrical

Power Supply	415V / 3 / 50 (V / Ø / Hz)
Plug Type	63A 5 Pin BS4343
Running Current	63 A

Physical

Noise Level	46 dBA @ 10 mtrs
Handling Options	Fork Pockets/4 point lifting eyes
Dry Weight	8000 Kg
Dimensions (Length)	6100 mm
Dimensions (Width)	2450 mm
Dimensions (Height)	2550 mm
Height of Flue Above Ground	3900 mm